300KG MAGLOCK



- · Dual voltage: 12/24VDC
- Current draw: 500mA/250mA
- · MOV surge protection
- · Lock type: Fail-safe
- Monitored with LED and NO and NC relay
- · Push-off button on armature for instant release
- CE approved
- Dimensions: 250mm (L) x 41mm (W) x 26mm (D)



The 300Kg electromagnetic locks offer a cost effective solutions with easy installation & suitable for variety of applications. Can be used for both inswing and out-swing doors.







| | | 1 |
|---|--|---------------|
| TOG DOOR AND G | CUSTO | |
| UNIT 10 SPENCER SQUARE , 6 SPENCER ROAD | | COMPANY NAME: |
| SALT RIVER | PHONE: 021 447 1328 | ADDRESS: |
| 7925 | WHATSAPP : 082 452 9696 | CONTACT: |
| | EMAIL: admin@tog.co.za; sales@tog.co.z | TEL: |
| FNB: 62089767910 | BR: 200309 | VAT NO: |
| VAT: 4930223401 | | YOUR REF: |
| | | |

| SUUKC | MACI | | CVCTEM | - DOUBLI |
|-------|------|------|-----------|----------|
| JUUNG | WAGL | .UCR | 3131 EIVI | - DUUDLI |

| 300KG MAGLOCK SYSTEM - DOUBLE | | |
|-------------------------------|--------------------------------|--|
| TOG CODE | ITEM DESCRIPTION | |
| RE-LK118 | MAGLOCK SP300KG WITH LED | |
| RE-LK118-1 | BRACKET ZL FOR SP300KG MAGLOCK | |
| RE-LK118-2 | L-BRACKET FOR SP300KG MAGLOCK | |
| RE-LK118-3 | U-BRACKET FOR SP300 MAGLOCK | |
| RE-PS49/1 | 12V DC POWER SUPPLY | |
| RE-BA13 | BATTERY FOR POWER SUPPLY | |
| ET-01221-000/TR | TX 1 BUTTON RC DUAL 434MHZ | |
| ET-00728-000 | RECIVER 1 CH ROLLING | |

















| _ | |
|--|--|
| | |
| | |
| MER DETAILS | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| F DOOD | |
| E DOOR | |
| PICTURE | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| t————————————————————————————————————— | |